

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Canceled)
2. (Currently Amended) A motor ~~according to Claim 1~~, comprising:
a rotor including a shaft and a magnet surrounding a portion of the shaft;
a stator surrounding the magnet of the rotor with a gap therebetween, and adapted
to generate a magnetic field thereby causing the rotor to rotate around an axis of the shaft;
a rotor sleeve having a cylindrical portion and a flange provided at one end of the
cylindrical portion, the rotor sleeve being provided between the magnet and the shaft so as to
fixedly hold the magnet and the shaft together;
a boss having a circular shape with a center hole for allowing the shaft to
rotatably pass therethrough, and being formed with the stator so as to oppose the flange of the
rotor sleeve; and
a plurality of bearing balls rotatably disposed between the boss and flange of the
rotor sleeve, wherein an inner surface of the boss is beveled to form a conical configuration with
a diameter increasing from the center hole of the boss.
3. (Currently Amended) A motor according to Claim ~~[[1]]~~ 2, further
comprising a thrust spring adapted to press the one end of the shaft by a rotatable ball.
4. (Currently Amended) A motor according to Claim ~~[[1]]~~ 2, wherein the
rotor sleeve has a plurality of partitioning protrusions formed on the flange, the partitioning
protrusions being adapted to prevent the bearing balls from coming in contact with one another
and to allow the bearing balls to freely rotate.
5. (Currently Amended) A motor according to Claim ~~[[1]]~~ 2, wherein the
boss has a plurality of partitioning protrusions formed on an inner surface thereof, the

partitioning protrusions being adapted to prevent the bearing balls from coming in contact with one another and to allow the bearing balls to freely rotate.

6. (Currently Amended) A motor according to Claim [[1]] 2, wherein the other end of the shaft is rotatably supported by a sleeve bearing.

7. (Currently Amended) A motor according to Claim [[1]] 2, wherein the rotor sleeve is formed by resin-molding such that resin is filled between the magnet and the shaft and cured thereby fixedly holding the magnet and the shaft together.

8. (Currently Amended) A motor according to of Claim [[1]] 2, wherein the shaft has a spiral ridge formed on a surface of an exposed portion thereof.

9. (Original) A motor according to Claim 8, wherein the spiral ridge is formed of resin.

10. (Original) A motor according to Claim 9, wherein the spiral ridge is resin-molded simultaneously when the rotor sleeve is formed such that resin is filled between the magnet and the shaft.

11. (Currently Amended) A motor according to Claim [[1]] 2, wherein the boss is formed by resin-molding integrally with the stator.

12. (Currently Amended) The motor of claim [[1]] 2, wherein the motor is a stepping motor.